

## Shell Kit Aqualift S Compact tileable GTF1200 Mono



## **Article information**

Item no.: 280501X-RBK GTIN: 4026092106952

Price group: 20

## **Description**

For combination with a KESSEL technology kit for creating a Mono lifting station for wastewater without sewage with a GTF1200 wastewater pump. The ready to plug in lifting station for wastewater without sewage is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an open pump tank. One-handed closures enable easy removal of the integrated components. The system for installation in the floor slab is pre-assembled for final installation on site. KESSEL shell kit consisting of:

- With vertically adjustable upper section for continuous height and level compensation and integrated floor drain - PE collection tank, resistant to aggressive wastewater and 3 m groundwater - Includes backflow preventer for the pressure pipe - Includes connection socket for inlet and conduit pipe

Variant

Type of system: Single unit
Rim width: Float switch
Backwater protection: integrated

General characteristics

Colour: black
Standard: EN 12050-2
Type of wastewater: without sew

Type of wastewater: without sewage Installation situation: floor slab installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Net weight: 15,2 kg
Gross weight: 15,2 kg
Groundwater resistant from lower edge of base 3000 mm

section:

Installation depth: 490 - 620 mm



Vertical adjustment: vertically adjustable upper section

Length:617 mmWidth:585 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Pressure pipe connection (DN): 32
Pressure pipe connection (OD): 40 mm
Inlet nominal size (DN): 100 mm
Pumping volume: 16 l
Tank volume: 65 l

Coverage features

Type of cover: tileable cover plate

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Drainage function:

Polymer
grey
366 mm
yes

Cover locking: Lock & Lift Load class: K 3 (EN 1253-1)

Max. flooring height: 16 mm

Pumping device

Pump control: GTF 1200

Number of pumps: 1
Max. pumping height: 9 m