

## Practicus basement drain DN 100, vert., Black slotted grating



### Article information

Item no.: 45210.40  
 GTIN: 4026092033005  
 Price group: 10

### Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

### Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

#### Variant

Contents of sludge trap:	no
Discharge rate (l/s) with 10 mm backwater:	1
Discharge rate (l/s) with 20 mm backwater:	2

#### General characteristics

Standard:	EN 1253-2
Nominal size (DN):	100
Outer diameter (OD):	110 mm

#### Dimensions

Vertical adjustment:	20 - 76 mm
Net weight:	1,12 kg
Gross weight:	1,18 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	180 mm
Installation depth:	221 - 277 mm
Vertical adjustment:	vertically adjustable upper section
Length:	135 mm
Width:	135 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Tank/drain body

Number of outlets:	1
Material of drain body:	PP
System:	vertical

## Coverage features

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	138 mm
Height of cover:	16 mm
Length of cover:	138 mm
Frame material:	Polymer
Cover locking:	screwed
Load class:	K 3 (EN 1253-1)
Rim length:	150 mm
Rim material:	150 mm
Shape of upper section:	square
Upper section material:	Polymer
Contents of sludge trap:	no
Odour trap:	included